

## TECHNICAL BULLETIN

## **Textile Processing Compound**

## Let You LEAD The Process

E-mail : contact@nestorindustries.com

## Nesto Soft BS

Micro amino silicone

	Provides excellent surface smoothness with bounciness
	✓ Imparts excellent surface softness to fabrics.
Features	✓ Improves sew ability.
	<ul> <li>Along with synthetic resin finishes improves the properties of goods</li> </ul>
	<ul> <li>Does not affect the brightness of dyed shades.</li> </ul>
	✓ Produces finish effects that are fast to washing and dry cleaning.
Туре	Non ionic
Constitution	Reactive polydimethyl siloxane.
Appearance	Clear Solution
рН	5.5 - 6.5
Solubility	Readily soluble in water.
Storage	Stable under normal conditions.
Application	
	(1) Padding on all types of fibres ;
	Nesto Soft BS - 2 to 5 gpl
	pH—5
	Pad : 65 – 85 % pick up
	Pad-dry-cure at 130 Deg.C.
	(2) Exhaust method ;
	<b>Nesto Soft BS</b> - 1- 2 % O. W. F.
	at pH 4.5 – 5.5
	for 25 -30 mins. At 30 – 40 Deg. C

The product appearance varies from batch to batch. The colour & viscosity may vary from batch to batch and its intensity is not an indication of product strength.

NONWARRANTY: The suggestions and data in this bulletin are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions on an experimental basis before adopting them on a commercial scale.

Head Office Address: Plot No- 538, GIDC, Pandesara, Surat- 394221 Contact No. - +91 8306083020, +91 9377781836  $\parallel$  Website : www.nestorindustries.com