

## C A R Solution

### High performance Core Alkali Removing Solution & Buffer

#### SPECIAL FEATURES:

- Provides efficient buffering system during dyeing and printing operations with good reproducibility.
- Non - volatile
- Regulates pH throughout the cycle of heating, cooling, steaming etc. during processing.
- Is safe on blends of polyester and viscose.
- Free from hazardous acids.

#### CHARACTERISTICS:

<i>Appearance</i>	:	Colourless liquid
<i>Ionic Nature</i>	:	Anionic
<i>Constitution</i>	:	Blends of surfactants & organic acids

#### APPLICATION:

1.0 to 2.0 g/l of **CAR Solution** in bath for Core Alkali Removing.

0.7 to 1.5 g/l of **CAR Solution** in dye bath. Always first add **CAR Solution** to dye bath, then dose in leveling agents, dyestuffs etc.

1.0 to 1.5% of **CAR Solution** in print paste.

<b>Storage</b>	Stable under normal conditions.
<b>Packing</b>	230 Kg Barrels / 50 Kg Plastic Carboy

The product appearance varies from batch to batch. The colour & viscosity may vary from batch to batch and its intensity is not an indication of product strength.

NONWARRANTY: The suggestions and data in this bulletin are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions on an experimental basis before adopting them on a commercial scale.

Head Office Address: Plot No – 538, GIDC, Pandesara, Surat – 394221  
Contact No. - +91 8306083020, +91 9377781836 || Website : [www.nestorindustries.com](http://www.nestorindustries.com)