



Nesto Lube CL

Fibre to Fibre & Fibre to Metal Lubricant

Nesto Lube CL is a high molecular weight polymeric based lubricant used for reducing cracks and crease marks in wet processing. It reduces the friction between both fiber to fiber and fiber to metal friction.

CHARACTERISTICS

Appearance	:	Clear to slightly hazy liquid
Chemical nature	:	Blend of high molecular weight polymers
Ionic nature	:	Nonionic
pH value	:	Approx 7.0
Dilution	:	In water in all proportions

ATTRIBUTES

- It provides exceptional fiber to metal and fibre-to-fibre lubricity.
- It prevents crush and crack marks.
- It is stable at high temperatures.

APPLICATIONS

Dosages

Desizing Bath	:	1-3% owg
Cellulase Bath	:	1-2% owg
Dye Bath	:	1-3% owg

HANDLING RECOMMENDATIONS

Direct contact with skin or eyes may cause irritation. If this occurs, flush thoroughly with water. If irritation persists, get medical attention.

The usual precautions in keeping chemicals away from the skin and eyes, avoid ingestion and prolonged inhalation of their vapors.

Storage	Stable under normal conditions.
Packing	50 Kg. Plastic Carboy

The product appearance varies from batch to batch. The colour & viscosity may vary from batch to batch and its intensity is not an indication of product strength.

NONWARRANTY: The suggestions and data in this bulletin are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions on an experimental basis before adopting them on a commercial scale.

Head Office Address: Plot No – 538, GIDC, Pandesara, Surat – 394221
Contact No. - +91 8306083020, +91 9377781836 || Website : www.nestorindustries.com